

Basis-Befehle

alias, unalias	create or remove a pseudonym for a command or series of commands
alias l='ls -al more'	gilt fuer KornShell (ksh)
alias l 'ls -al more'	gilt fuer C Shell (csh)
banner	make posters
banner "BRE / HAM"	max. 10 Zeichen (Texthoehe = 7 Zeilen)
cd , chdir	change working directory
cd	zum Home-Verzeichnis
cd /usr1/cadds/parts	zu einem Verzeichnis / absolute Pfadangabe
cd ..	eine Verzeichnis-Ebene zurueck
clear	clear the terminal screen
cp	copy files
cp -r dir1 dir2	Verzeichnis "dir1" wird komplett kopiert auf den Namen "dir2"
cp file1 file2	File kopieren
date	write the date and time
df	report number of free disk blocks and files
df -k	listet in Masseinheit "kbytes"
du	display the number of disk blocks used per directory or file
du -a -k *	auslisten aller Verzeichnis-Strukturen mit Dateigroesse
du -s -k *	Gesamtgroesse eines Verzeichn.
file	determine file type
file *	auslisten aller File-Typen im Verzeichnis

Basis-Befehle

find	find files
find . -name filename -print	
finger	display information about local and remote users
finger cvjjj	Infos zur UserID "cvjjj"
grep	search a file for a pattern
grep 'xxx' *	suche das Muster xxx in allen Files
head	display first few lines of file
history	process command history list
last	display login and logout information about users and terminals
last -n 10	die letzten 10 Eintraege
logout	exit from a login session
ls	list contents of directory
ls -al	listet alle Eintraege
ls -al more	listing / seitenweise
man	find and display ref. manual pages
man ls	Doku fuer das Kommando "ls"
mkdir	make directories
more	browse or page through a text file
mv	move files
mv oldfile newfile	Umbenennen eines Files

Basis-Befehle

passwd	change login password and password attributes
ps	report process status
ps -ef	auslisten aller Prozesse
pwd	return working directory name
rm , rmdir	remove directory entries
tail	deliver the last part of a file
textedit	XView-based text editor with mouse support
uname	print name of current system
uname -a	alle Informationen
vi, view, vedit	screen-oriented (visual) display editor based on ex
which	locate a command; display its pathname or alias
who	who is on the system
whoami	display the effective current username
whodo	who is doing what

Basis-Befehle

lp, cancel send/cancel requests to an LP print service
lp -d printername filename

lpstat print information about the status of
 the LP print service
lpstat -p printername

SPECIALS / SUN

dmesg collect system diagnostic messages to
 form error log

prtconf print system configuration